

Set Application-Level Configuration Properties

If you have the Service Administrator role, or the Power User role for applications that you created, you can customize Oracle Essbase using application-level configuration properties. Application-level configuration properties apply to all cubes in the application.


One way to specify configuration properties of an application is to do it prior to building the application and cube, using the application workbook. To see an example, go to Files in the Essbase web interface, and download the application workbook `Sample_Basic.xlsx`. It is located in the gallery, in the Demo Samples section (under Block Storage). In this application workbook, go to the `Cube.Settings` worksheet. Under Application Configuration, the `DATACACHE`SIZE property is set to 3M, and the `INDEX`CACHE SIZE property is set to 1M.

38	Application Configuration	
39		
40	DATACACHE SIZE	3M
41	INDEX CACHE SIZE	1M
42		
43		
<div><div>◀ ▶</div><div>Essbase.Cube</div><div>Cube.Settings</div><div>Cube.Generations</div><div>D</div></div>		

The following steps tell you how to configure an application that is already deployed, by adding properties and their corresponding values in the Essbase web interface.


1. On the Applications page, select the application you want to configure.
2. Click **Configuration**.
3. To add a property, click **Add**.

Scroll through the list or search for a property.


4. Click  to add the property to the list.

51


A	ASOBUFFERCOMMITWAIT	+
A	ASOCACHECONCURRENTCONSUMINGTHREADS	+
A	ASODEFAULTCACHESIZE	+

5. Click  to close the search tool.





51



Close

A	ASOBUFFERCOMMITWAIT	+	
---	---------------------	---	---

6. In the **Value** column, double click to enter a value.

 Configuration
  Variables
  Permissions
  Settings

Reset

Apply

Property ^	Value
ASODEFAULTCACHESIZE	200

7. When you're finished making changes, click **Apply and Restart**.

Note

If the application is not started, you are given the option to "Apply" rather than "Apply and Restart." Changes will be applied the next time the application is restarted.

8. Wait for the confirmation message.

✔ Configuration settings were stored successfully and will be applied when the application is restarted

For syntax and information about each of the application configuration properties you can use, see [Config Settings List](#). You do not need to use the optional [<appname>] syntax when adding properties to the application configuration.

Oracle does not recommend that you modify `essbase.cfg` on the Essbase file system. This configuration is automatically set.